

C3S

Static White
6° Narrow Spot


Project Name

Type



Input Requirements

835 Lumens	120 VAC/0.2A/21W
	240 VAC/0.1A/21W
	277 VAC/0.1A/21W
650 Lumens	120 VAC/0.2A/15W
	240 VAC/0.1A/15W
	277 VAC/0.1A/15W



Enter Catalog Number Sequentially from Left to Right

C3S - - -

Model	Lumens/CRI	CCT	Adaptor	Dimming	Level	Options	Voltage	Finish	Optics
C3S	L08	835/90	27	2700	9TC BusRun Clipless	E ELV 1 1%	P* Potentiometer	A 120	P White 6 6°
	L06	650/90	30	3000	9TD BusRun Deep		R** Rotation Lock	D 240	MB Black
			35	3500	9TS BusRun Shallow		SP* Switch w/ Potentiometer	F* 240	BR Brushed
			40	4000			SR** Switch w/ Rotation Lock	C 277	CP Custom
			9HC BusRun Clipless w/ Driverbox	E ELV 0 10%	N Local				
			9HD BusRun Deep w/ Driverbox	W Wire-less	C Casambi				
			9HS BusRun Shallow w/ Driverbox		Z Zigbee				
			BT Basic Track		T Lutron Athena				
			ST2 2-Circuit Stucchi	E ELV 0 10%	N Local				
			ST3 3-Circuit Stucchi	N Local					
			3L 5" Canopy	Z 0-10 1 1%					
			5L 3.5" QC Canopy	M DMX D Dark					
			7L 2" QC Canopy (Remote Driver Only)	D DALI					

Flush Fit BusRun Adaptor

Litelab's flush fit BusRun adaptor recesses entirely inside BusRun to provide a clean aesthetic. It is available with a Switch and Rotation Lock or On-Board Potentiometer for individual fixture dimming. BusRun fitters are available dimmable to 1% and can be dimmed proportionally using an ELV dimming system.

Dimming Note

This fixture is provided with LED Drivers suitable for the dimming protocol specified. Dimming performance may vary based on dimmer model or system being used. If exact dimming performance is required, Litelab recommends testing the Litelab fixture with the specified dimmer.

Accessories: See Page 5

- ☐ OL-DF-g Beam Softening Film
- ☐ OL-TD-g Beam Softening Lens
- ☐ OL-10x40-g Linear Spread Lens
- ☐ OL-10x60-g Linear Spread Lens
- ☐ OL-30x60-g Universal Spread Lens
- ☐ LVH/g Hexell Louver
- ☐ CHB/g-2 Crosshair Baffle




251 Elm Street, Buffalo, NY 14203 USA
800-238-4120 | www.litelab.com



Edition Date: 07/14/2021

Fitter Guide


9TC* - 120/240/277v Recessed BusRun Fitter - ELV Dimmable Only - 1%




Universal Voltage Fitter, Available with an optional Switch and Rotation Lock or Potentiometer - Dimmable to 1%.

Switch not available for 277 V.


9H - Wireless Control Fitter for BusRun




Basic Track - ELV Dimmable Fitter



Stucchi - 2-Circuit ELV & 0-10V Dimmable Fitter




Stucchi - 2-Circuit 0-10V, DMX and Dali Dimmable Fitter




Fitter Guide


Stucchi - 3-Circuit ELV & 0-10V Dimmable Fitter



Stucchi - 3-Circuit 0-10V, DMX and Dali Dimmable Fitter




-5L - 3-1/2" Dia. Quick Connect Canopy



-5 Remote Driver


- (1) 4" sq x 2-1/8" J-Box
- (1) 4" sq x 1-1/2" Extension Box

-3L - 5" Dia. x 1/4" H. Machined Canopy




-3 Remote Driver

- (1) 4" sq x 1-1/2" Extension Box




-5L ELV Driver

- (1) 4" sq x 2-1/8" J-Box
- (2) 4" sq x 1-1/2" Extension Box




-3L ELV Driver

- (1) 4" sq x 2-1/8" J-Box
- (2) 4" sq x 1-1/2" Extension Box



-5L 0-10v, DALI and DMX Driver

- (1) 4" sq x 2-1/8" J-Box
- (3) 4" sq x 1-1/2" Extension Box



-3L 0-10v, DALI and DMX Driver

- (1) 4" sq x 2-1/8" J-Box
- (3) 4" sq x 1-1/2" Extension Box


Photometrics

C3S-L06 6° Narrow Spot

Mounting Height in feet / meters	FC / Lux	Diameter in feet / meters
6.0' / 1.8m	707.8 f.c. / 7,618.7 lux	1.6' / 0.5m
8.0' / 2.4m	398.1 f.c. / 4,285.1 lux	2.1' / 0.6m
10.0' / 3.0m	254.8 f.c. / 2,742.6 lux	2.6' / 0.8m
12.0' / 3.7m	177.0 f.c. / 1,905.2 lux	3.2' / 1.0m
14.0' / 4.3m	130.0 f.c. / 1,399.3 lux	3.7' / 1.1m
16.0' / 4.9m	99.5 f.c. / 1,071.0 lux	4.2' / 1.3m

CBCP:	24,481 Cd
Efficacy:	40.8 lm/w
Delivered Lumens:	416 lm

C3S-L06 6° Narrow Spot - Polar Diagram



Accessories



FIXTURE SIZE CODE (G): Ø2.529" [64mm]

CUSTOM DISTRIBUTION FILMS AVAILABLE ON REQUEST.

OL-DF-G (DIFFUSION FILM)

DIFFUSION FILM: 0.25MM (0.01") FILM SOFTENS BEAM EDGES (FOR USE WITH MULTIPLE MEDIA)



DISTRIBUTION DIAGRAM



OL-TD-G (POLYCARBONATE DIFFUSION LENS)

DIFFUSION FILM: 3MM (0.1") TEXTURED LENS SOFTENS BEAM EDGES (FOR STANDALONE USE)



DISTRIBUTION DIAGRAM



OL-10x40-G (LINEAR SPREAD LENS)

40° LINEAR SPREAD LENS: 3MM (0.1") ELLIPTICAL SPREAD FOR LONG / LINEAR OBJECTS



DISTRIBUTION DIAGRAM



OL-10x60-G (LINEAR SPREAD LENS)

60° LINEAR SPREAD LENS: 3MM (0.1") ELLIPTICAL SPREAD FOR LONG / LINEAR OBJECTS



DISTRIBUTION DIAGRAM



OL-30x60-G (UNIVERSAL SPREAD LENS - INCLUDED)

UNIVERSAL SPREAD LENS: 3MM (0.1") LENS SPREADS LIGHT UNIVERSALLY FOR WIDER DISTRIBUTION

DISTRIBUTION DIAGRAM



LVH/G (HEXCELL LOUVER)

HEXCELL LOUVER: 3MM (0.1") MATTE BACK FINISH, 45° GLARE CUTOFF FOR VISUAL COMFORT

